TECHNICAL DATA SHEET:

AF3000 COLD SPRAY GALVANIZING COATING

AF3000 Shiny Galvanizing Spray is a shiny, light gray dried paint film that contains 65% zinc max. This galvanizing spray conforms to ASTM A780-92A.

A shiny zinc enhanced zinc coating that prevents rust and provides excellent outdoor protection. This is the product of choice for the cosmetic restoration of galvanized metal, chain link fences, and guard rails. Does not meet specifications calling for 65% zinc in the can or greater than 90% zinc in the dried paint film. Fast dry, prevents rust, and has excellent outdoor durability.



Made in the USA

APPLICATIONS

- Telecom Towers
- All Vehicle Bodies
- Agricultural, Mining & Construction Equipment

- Piping, Storage Tanks
- Bridges
- Ships & Marine Equipment

PROPERTIES

Coverage	Up to 15 Square Feet
Cleanup	Paint or LacquerThinner
Flammability	Extremely Flammable
Flash Point	-4°F
Specific Gravity	0.78
Solids Content	23%
Zinc in Dried Paint Film	4%
MIR Value	1.16, Cannot Exceed 1.25
HAPs Content	32%
Storage Temperature	40°F to 100°F
Application Temperature	50°F to 90°F
Heat Resistance	250°F
Resin System	Alkyd
Shelf Life	2 Years
Food Contact Rating	No

GLOSS INFORMATION

Gloss*: Flat < 15
*as measured on a 60 degree gloss meter.

DRY TIME*

*At 72°F, 50% hummidity, 1.5 mil thickness.

To Touch	10 Minutes
To Recoat	Anytime

www.allfasteners.com | Customer Service 888 859 6060